

Test Results and Modeling of the Honda Insight using ADVISOR

Kenneth J. Kelly

Matthew Zolot

National Renewable Energy Laboratory

Arthur Hieronymus

Gerard Glinsky

Environmental Testing Corp.

SAE - Future Transportation Technology Conference

Costa Mesa, CA


August 22, 2001








NREL Vehicle Testing and Modeling Interdisciplinary






Vehicle Systems Analysis



Vehicle Climate Control





Battery Thermal Management







Vehicle Testing Objectives

Measure the impact of air-conditioning on fuel economy and emissions

Study the behavior of the battery pack under various conditions

Develop temperature dependent battery pack model(s) for ADVISOR

Model correlation and development of accurate ADVISOR vehicle model







NREL's Vehicle Testing Partner:

Environmental Testing Corp (ETC)

Private emissions certification and R&D laboratory

Located 30 minutes from NREL in Aurora, Colorado

Key ETC customer: Daimler/Chrysler (on-site testing presence)

Customers Served in 2000 include:

Ford, Daimler/Chrysler, GM, Volvo, Jaguar, Hyundai, Isuzu

Recognized by EPA for High Altitude Emissions Certification

Previous NREL/DOE Experience testing Alternative Fuel Vehicles









NREL, CENTER

OLOGIES AND SYSTEMS



Environmental Testing Corp (ETC) : Capabilities

- 40,000 sq ft (3700 m²) test facility on 5 acres
- Emissions Certification and Fuel Economy
 - Four independent, temperature-controlled chassis test cells (-45 to 45 C) including 48" electric dynamometer
 - bag, modal and second-by-second analysis
 - chemical analysis laboratory
 - user defined driving cycles and temperatures
 - catalyst efficiency
 - diesel particulate
 - customizable data acquisition
- Evaporative Emissions, Running Loss, and On-Board Refueling Vapor Recovery (ORVR)
- Engine Dynamometer Testing
- Drivers Aid and Dynamometer Control Software







Vehicle Testing Data Acquisition

Battery temperatures, voltages, and currents (20 Hz)

- 30 cell temperatures
- 10 cell voltages
- inverter current
- auxiliary load current

Cabin temperatures

driver, passenger, roof console

Vehicle Operating Parameters

engine speed, map,
 vehicle speed, throttle
 position, engine coolant,
 intake air temp, O2

Emissions Data (20Hz, bag, and modal analysis)







Vehicle Testing Test Procedures

Chassis Dynamometer Test Procedures

- FTP-75
- US06 (0, 20, 40 degrees C)
- SC03 (95 degrees F, with and without A/C)
- HWFET



On-Road Testing

- Acceleration Tests
- City Driving Cycles (AC on/off)
- Highway Driving Cycles (AC on/off)
- Mountain Driving

Off-board Battery Testing

- Scheduled to begin in December '00
- ABC 150 Pack Testing


charge resistance, pulse power, Ah capacity, driving profiles

- Calorimeter Testing
- Airflow testing





Insight Fuel Economy Testing Results











Battery Pack Energy Usage



Insight Test Data Control Strategy Considerations




Insight Test Data Control Strategy Considerations





Insight Test Data On Road Driving





Speed

— SOC


Imotor

Elevation




Insight Test Data On Road Driving - NREL to VAIL







Insight Test Data Battery Temperature Effects




Insight Test Data - Air Conditioning SC03 with AC on (blue) and AC off (red)





Insight Road Test Denver City Driving - AC on/off




... including an updated version of the Honda Insight model










NREL, Center for Transportation Technol











Fuel Economy Comparison Insight Test Data vs. ADVISOR





Comparison of ADVISOR Simulation to Test Data





Status and Conclusions

Insight testing is complete an updated model now available in ADVISOR 3.2 release

Insight showed 33% drop in fuel economy with Air Conditioning

Battery Pack Control Limits - 60% of 6.5 Ah (144 V)

Insight exhibited adequate battery thermal management design under moderate conditions.

Insight failed to meet US06 aggressive driving trace - problem was exacerbated by:


- low temperature battery internal resistance
- high temperature power limiting for temperature control

Latest ADVISOR model of Insight accurately predicts overall fuel-use and component behavior





Future Directions





Acknowledgements

DOE - Office of Advanced Automotive Technologies
Bob Kirk - Program Manager

Battery Thermal Management Team at NREL

Environmental Testing Corporation - Aurora, CO

Argonne National Laboratory



